



SOLAR BATTERY

An Ideal Solution for
Storage of Solar Energy



High-Tensile
Resistance



Largest Service
Network



Environment
Friendly



Longest
Warranty



Hassle Free &
Doorstep
Maintenance



Low Self
Discharge

#MorePowerToYou

SOLAR TUBULAR BATTERY

Technical Specification

Model Name	Warranty (in Months)	Capacity C10 @ 27 C	Capacity C20 @ 27 C	Dimensions in (mm)			Charging Current (Amps)
				L	W	H	
TPXS40	72*	40Ah	50Ah	410	175	230	4
TPXS120	72*	120Ah	150Ah	490	180	390	12
TPXS150	72*	150Ah	190Ah	490	180	390	15

*Conditions Apply

PRODUCT FEATURES

- Using best grade PP containers and lid
- Tubular positive plate made with PDC Machine of ZIBO
- High tensile resistance / Porosity polyester gauntlets
- High Porosity PE Envelope separators from DARAMIC, USA
- Micro porous ceramic vent plug
- Heavy duty terminals
- SS fasteners
- Double side pasting negative plate



Channel Partner/Dealer



www.teslapowerusa.in
support@teslapowerusa.com
☎ +91 9090905599

APAC Office:
#1003-4-5, Tower-1,
DLF Corporate Greens,
Sector 74A, Gurugram,
Haryana-122004 (INDIA)

Corporate Office:
Suite #635 S 4000,
Hollywood Blvd Hollywood,
Florida, USA- 33021

Registered Office:
358/3524, Silverside Road,
Wilmington, Delaware,
U.S.A. -19810-4929